



AUMARK



AUMARK
3-150-MT

3-150-MT

Drive style	4x2
Steering wheel position	Right hand
MASS	
Manufacturer's Gross Vehicle Mass (GVM)	6,900
Manufacturer's Gross Combination Mass (GCM)	8,000
Manufacturer's Front Axle Mass (GA Front)	2,500
Manufacturer's Rear Axle Mass (GAU Rear)	4,500
Permissible Gross Vehicle Mass (V)	6,900
Permissible Gross Combination Mass (D/T)	8,000
Permissible Front Axle Mass (A Front)	2,500
Permissible Rear Axle Mass (A Rear)	4,500
Unladen Front Axle Mass (T Front)	1,540
Unladen Rear Axle Mass (T Rear)	780
Unladen Mass Total (Tare)	2,320
DIMENSIONS	
Overall Length(OL)	5,945
Overall Width(OW)	2,136
Overall Height(OH)	2,180
Front Overhang(FOH)	1,095
Rear Overhang(ROH)	1,420
Wheelbase (WB)	3,360
Cab to End of Chassis(CE)	4,205
Cab to Rear Axle(CA)	2,785
Turning Radius(TR)	6.75
Fuel Tank Capacity(FTC)	80
PERFORMANCE	
Maximum Speed	108km/h
Gradeability at V	30%
ENGINE	
Make	CUMMINS
Model	ISF2.8s3148T
Max Power- Kw@R/Min	110/3200
Max Power-HP @ R/Min	150/3200
Max Torque-N.M @ R/Min	360/1800-2700
Cylinder	4
Capacity	2.78

TRANSMISSION	
Make	ZF
Model	ZF5S368
Type	5 Speed Manual
Forward Ratios	5.762, 2.922, 1.638,1, 0.782
Reverse Ratio	5.149
CLUTCH	
Diameter	308mm
Type	Single Plate
Operation	Diaphragm Spring
AXLE	
Front Axle	Forged I-Beam
Rear Axle	Integral
Rear Axle Ratio	4.875
SUSPENSION	
Front	Leaf Spring
Rear	Leaf Spring
Brakes	
System Type	Full Air - Dual Circuit
Emergency	Spring Potential Brake
Auxiliary	Exhaust Brake
ABS	Yes
CAB	
Cab Control	Forward Tilt Cab
No. of Seats	3
ELECTRICAL SYSTEM	
System Voltage	24V
No. of Batteries	2 X 12V
TYRE	
Tyre Size	7R16-14PR
Type	Radial
WARRANTY	2 Year/ Unlimited Mileage

AUMARK